

## 495SKSP combination strobe horn

### 495S Strobe:

- built-in RFI filters
- Indoor / Outdoor use
- solid state power supply
- xenon strobe lamp
- two year warranty on power supply
- one year warranty on lamp
- available in six lens colors
- UL listed (all models)

Height: 9 1/4"  
 Depth: 4 3/4"  
 Width: 5"



The MICROSTROBE® family is a low profile, single flash, low cost strobe light which features a plug-in replaceable lamp and Lexan® lens. The high efficiency, solid state, power supply is fully potted in polyurethane for the ultimate in protection from moisture and vibration. All units are polarity protected and have built-in filters to protect against radio interference and spike voltages.

120 VAC Voltage and Amperage 120VAC draws 0.07A average for strobe only.  
 Power Supply Output 2.7 Watts 1.9 joules per flash  
 Flash Rate 60 to 80 flashes per minute  
 Size and Weight 5" tall x 3" dia. x 0.5 lbs for strobe only  
 24 VDC Voltage and Amperage 12-80VDC draws 0.4A average @ 12VDC, 24VDC is 0.2A for strobe only  
 Power Supply Output 2.7 Watts 1.9 joules per flash  
 Flash Rate 60 to 80 flashes per minute  
 Size and Weight 5" tall x 3" dia. x 0.6 lbs for strobe only

### KSP Electronic Horn:

#### Description:

The KSP are low current, medium decibel, electronic horns for medium duty use. Has Adjustable dB level from the maximum 95 dB at 10 feet level. Provides 4 different sounds in 1 unit. Choose from the "SB" or the "TB" sound group. SB= ambulance siren, police siren, telephone ring, and melody. TB= pulsing sounds of Fast, Slow, High, Low  
 Low current consumption  
 Simple connection

The PVC weatherproof enclosure used in the above assembly, suitable for indoor or outdoor use, is durable and corrosion resistant. Mount on flat surface, or drill holes for other mounting options. Volume is adjustable from the 95 dB at 10 feet maximum rated output.

