

**PRE Series**

**ø56mm LED Tower Light**



**Ordering information**

	<b>PRE</b>	<b>F</b>	<b>3</b>	<b>02</b>	<b>RYG</b>
	①	②	③	④	⑤
①	PME ø 45mm LED Tower Light	PRE ø 56mm LED Tower Light			
②		Steady light	F	Flashing light	
③			1	1 Stack (Red)	
			2	2 Stack (Red+Green)	
			3	3 Stack (R+Amber+G)	
			4	4 Stack (R+A+G+Blue)	
			5	5 Stack (R+A+G+B+Clear)	
④			01	12VAC/ DC	
			02	24VAC/ DC	
			10	120VAC	
			20	240VAC	
⑤			R	Red lens	
			G	Green lens	
			A	Amber lens	
			B	Blue lens	
			C	Clear lens	

See page 10 for Mounting options  
Available Buzzer kits(MPZ 56E) for PRE series

**Specifications**

Series	PME series	PRE series
Power supply	12VAC/DC, 24VAC/DC, 120VAC, 240VAC	
IP level	IP 56	
Lens color	Red, Green, Amber, Blue, Clear	
Flash rate	80 / min	
PME series Current consumption	1Stack	12V:41mA, 24V:27mA, 120V:28mA, 240V:28mA
	2Stack	12V:89mA, 24V:57mA, 120V:60mA, 240V:60mA
	3Stack	12V:149mA, 24V:95mA, 120V:99mA, 240V:99mA
	4Stack	12V:204mA, 24V:125mA, 120V:131mA, 240V:131mA
	5Stack	12V:240mA, 24V:155mA, 120V:163mA, 240V:163mA
PRE series Current consumption	1Stack	12V:54mA, 24V:28mA, 110V:25mA, 240V:25mA
	2Stack	12V:109mA, 24V:62mA, 110V:57mA, 240V:57mA
	3Stack	12V:169mA, 24V:102mA, 110V:91mA, 240V:91mA
	4Stack	12V:223mA, 24V:136mA, 110V:124mA, 240V:124mA
	5Stack	12V:275mA, 24V:169mA, 110V:155mA, 240V:155mA
Bulb type	LED Modular	
Buzzer kit	No buzzer	Available MPZ 56E Not for 12 volt units
Sound level	No buzzer	80 dB(85mA)
Termination	Wire leads	
Approvals	CE	

**Features**

- Prism-cut lenses for even light distribution
- Selectable Base, Pole or Wall bracket mounting
- Steady and flashing models
- 5 stack light color available
- Various operating voltage available
- Buzzer kit(MPZ 56E) adaptable for PRE series
- LED light provide long life and reliability

**Dimensions**

(UNIT: mm)

